

Track				
By Roll-Out			Speed (Km/hr)	
Ratio	Roll-out (m)	Gear Inches	100 RPM	120 RPM
49x14	7.48	94.50	44.9	53.9
48x14	7.32	92.50	43.9	52.7
47x14	7.17	90.60	43.0	51.6
50x15	7.12	90.00	42.7	51.3
49x15	6.98	88.00	41.9	50.3
48X15	6.84	86.40	41.0	49.2
47x15	6.69	84.60	40.1	48.2
50x16	6.68	84.40	40.1	48.1
49x16	6.54	82.90	39.2	47.1
48x16	6.41	81.00	38.5	46.2
50x17	6.28	79.40	37.7	45.2
47x16	6.28	79.30	37.7	45.2
49x17	6.16	77.80	37.0	44.4
48x17	6.03	76.00	36.2	43.4
47x17	5.91	74.60	35.5	42.6
49x18	5.82	73.50	34.9	41.9
48x18	5.70	72.00	34.2	41.0
47x18	5.58	70.50	33.5	40.2

Track				
By Front Chainring			Speed (Km/hr)	
Ratio	Roll-out (m)	Gear Inches	100 RPM	120 RPM
50x17	6.28	79.40	37.7	45.2
50x16	6.68	84.40	40.1	48.1
50x15	7.12	90.00	42.7	51.3
49x18	5.82	73.50	34.9	41.9
49x17	6.16	77.80	37.0	44.4
49x16	6.54	82.90	39.2	47.1
49x15	6.98	88.00	41.9	50.3
49x14	7.48	94.50	44.9	53.9
48x18	5.70	72.00	34.2	41.0
48x17	6.03	76.00	36.2	43.4
48x16	6.41	81.00	38.5	46.2
48X15	6.84	86.40	41.0	49.2
48x14	7.32	92.50	43.9	52.7
47x18	5.58	70.50	33.5	40.2
47x17	5.91	74.60	35.5	42.6
47x16	6.28	79.30	37.7	45.2
47x15	6.69	84.60	40.1	48.2
47x14	7.17	90.60	43.0	51.6